



ARMAKLEEN™ Rust Remover

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ARMAKLEEN Rust Remover

SYNONYM(S): Not available.

PRODUCT PART NUMBERS: 6347, 6447

PRODUCT USE: Aqueous, acidic concentrated rust remover and cleaner that is to be diluted with water.

**24-HOUR EMERGENCY PHONE NUMBERS
MEDICAL AND TRANSPORTATION (SPILL):**

These numbers are for emergency use only. If you desire non-emergency product information, please call a phone number listed below.

1-800-468-1760

MANUFACTURER:
The ArmaKleen Company
469 North Harrison Street
Princeton, NJ 08543
USA
(609) 683-5900

SUPPLIER:
Safety-Kleen Systems, Inc.
5360 Legacy Drive, Building 2, Suite 100
Plano, TX 75024
USA
(800) 669-5740

TECHNICAL INFORMATION: 1-800-332-5424

SAFETY-KLEEN MSDS FORM NUMBER: 82949
THE ARMAKLEEN COMPANY MSDS NUMBER: 817

ISSUE: March 2, 2011

ORIGINAL ISSUE: September 17, 2003

SUPERSEDES: February 22, 2008

PREPARED BY: ArmaKleen MSDS Coordinator

APPROVED BY: The ArmaKleen Company

ARMAKLEEN Rust Remover

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

WT%	NAME	SYNONYM	CAS NO.	OSHA PEL*		ACGIH TLV®		LD ^a	LC ^b
				TWA	STEL	TWA	STEL		
60 to 100	Phosphoric Acid	Orthophosphoric acid	7664-38-2	1mg/m ³	N. Av.	1mg/m ³	3mg/m ³	1530	>850
1 to 5	Gluconic Acid	D-Gluconic Acid Solution	526-95-4	N. Av.	N. Av.	N. Av.	N. Av.	7630	N. Av.
1 to 5	Alcohols C9-C11, ethoxylated	Linear, primary alcohol ethoxylate	68439-46-3	N. Av.	N. Av.	N. Av.	N. Av.	1378	N. Av.
1 to 5	Propylene glycol ether	N. Av.	29911-28-2	N. Av.	N. Av.	N. Av.	N. Av.	1620	N. Av.
1 to 5	Lauramine Oxide	Lauryl Dimehtylamine Oxide	1643-20-5	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.

N.Av. = Not Available

^aOral-Rat LD₅₀ (mg/kg)

^cParticulates not otherwise classified

^bInhalation LC₅₀(mg/m³)

*OSHA Final PEL value (enforceable). Some States have adopted more stringent values.

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

APPEARANCE

Liquid, clear, light straw color, and mild detergent odor.

WARNING!

HEALTH HAZARDS

May be harmful or fatal if swallowed.

May irritate or burn the respiratory tract (nose, throat, and lungs), eyes, skin, and digestive tract.

Contains material which can cause eye, skin, and digestive tract damage.

ENVIRONMENTAL HAZARDS

Toxic to aquatic life.

POTENTIAL HEALTH EFFECTS

INHALATION

Vapor or mist may irritate the respiratory tract (nose, throat, and lungs).

(BREATHING):

Vapor or mist may cause sore throat, coughing, shortness of breath, and/or burns to mucous membranes.

EYES:

May cause irritation, redness, pain, blurred vision, burns, and/or damage.

SKIN:

May cause irritation, redness, pain, blistering, and/or burns. Latent effects are possible. Not likely to be absorbed through the skin in harmful amounts

INGESTION

May be harmful or fatal if swallowed. May cause painful swallowing,

ARMAKLEEN Rust Remover
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

(SWALLOWING): nausea, vomiting, and/or stomach pains. May cause mouth, throat, and/or gastrointestinal burns. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

CHRONIC: Prolonged or repeated inhalation may cause burns to mucous membranes. Eye contact if not treated immediately may result in burns and permanent damage. Prolonged or repeated skin contact may cause drying, cracking, redness, itching, swelling (dermatitis), and/or burns.

CANCER INFORMATION: No known carcinogenicity. For more information, see **SECTION 11: CARCINOGENICITY**.

POTENTIAL ENVIRONMENTAL EFFECTS
Not available. Also see **SECTION 12: ECOLOGICAL INFORMATION**.

SECTION 4: FIRST AID MEASURES

INHALATION: (BREATHING) Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if breathing difficulty persists.

EYES: If irritation or redness from exposure to vapor develops, move away from exposure into fresh air and flush eyes with water for 5 minutes. Upon direct contact with liquid, immediately flush eyes with plenty of water for 15 minutes while holding eyelids apart. Get medical attention.

SKIN: Remove affected clothing and shoes. Wash skin thoroughly with soap and water. Get medical attention if irritation or pain develops or persists.

INGESTION: (SWALLOWING) Immediately get medical attention. Call medical emergency telephone number (1-800-468-1760) for additional information. **DO NOT** induce vomiting. If spontaneous vomiting occurs, keep head below hips to avoid breathing the product into the lungs. Never give anything to an unconscious person by mouth.

NOTE TO PHYSICIANS: Treat symptomatically and supportively. Avoid gastric lavage. Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760.

ARMAKLEEN Rust Remover
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: greater than 212°F (100°C)

FLAMMABLE LIMITS IN AIR: Not applicable.


AUTOIGNITION TEMPERATURE: Not applicable.

HAZARDOUS COMBUSTION PRODUCTS: Product itself does not burn, but may decompose upon heating to produce carbon monoxide, carbon dioxide, and oxides of potassium.

CONDITIONS OF FLAMMABILITY: Product will not burn.

EXTINGUISHING MEDIA: Not applicable.

NFPA 704 HAZARD IDENTIFICATION: This information is intended solely for the use by individuals trained in this system.



FIRE FIGHTING INSTRUCTIONS: Keep storage containers cool with water spray. A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

FIRE AND EXPLOSION HAZARDS: Heated containers may rupture. "Empty" containers may retain residue and can be hazardous. Not sensitive to mechanical impact or static discharge.

ARMAKLEEN Rust Remover

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

SECTION 6: ACCIDENTAL RELEASE MEASURES

Spilled product is slippery. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain away from surface waters and sewers. Neutralize the spill with sodium bicarbonate (such as Arm & Hammer baking soda) to raise the pH to a neutral 7.0. Pour copious amounts of powdered sodium bicarbonate (baking soda) directly onto the spilled Rust Remover, let the sodium bicarbonate stand for several minutes on the spilled rust remover and then wipe up the neutralized spill residue.

Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

There may be additional regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see **SECTION 15: REGULATORY INFORMATION**.

SECTION 7: HANDLING AND STORAGE

HANDLING: When diluting, cautiously mix product and water together while stirring. Do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes.

SHIPPING AND STORING: Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Empty product containers may retain product residue and can be hazardous. See **SECTION 14: TRANSPORT INFORMATION** for Packing Group information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: Use NIOSH-certified, combination N-, P-, or R- series particulate filter respiratory protective equipment when concentration of vapor or mist exceeds applicable exposure limits. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.

EYE Where eye contact is likely, wear chemical goggles; contact lens

ARMAKLEEN Rust Remover

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

PROTECTION: use is not recommended.

SKIN PROTECTION: Wear nitrile, neoprene, or equivalent protective gloves; use of polyvinyl alcohol (PVA), natural rubber, or equivalent gloves is not recommended.

To avoid skin contact where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, whole body suits, or other protective clothing.

PERSONAL HYGIENE: Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse. Discard affected clothing, shoes, or protective equipment if they cannot be thoroughly cleaned. Discard leather articles, such as shoes, saturated with the product.

OTHER PROTECTIVE EQUIPMENT: Facilities storing or using this product should be equipped with an emergency eyewash and shower, in the immediate work area.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES
--

PHYSICAL STATE, APPEARANCE, AND ODOR:	Liquid, clear, light straw color, and mild detergent odor.
ODOR THRESHOLD:	Not available.
MOLECULAR WEIGHT:	Not applicable.
SPECIFIC GRAVITY:	1.43 (water = 1)
DENSITY:	11.94 LB/US gal (1433 g/L)
VAPOR DENSITY:	less than 1 (air = 1)
VAPOR PRESSURE:	17.5 mm Hg at 68°F (20°C) (approximately)
BOILING POINT:	212°F (100°C)
FREEZING/MELTING POINT:	32°F (0°C)
pH:	<1.0 concentrate; 1.39 (5% solution)
EVAPORATION RATE:	Less than 1 (butyl acetate = 1)
SOLUBILITY IN WATER:	Complete.
FLASH POINT:	greater than 212°F (100°C)
FLAMMABLE LIMITS IN AIR:	Not applicable.

ARMAKLEEN Rust Remover
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

AUTOIGNITION TEMPERATURE: Not applicable.

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal temperatures and pressures.

INCOMPATIBILITY: Avoid oxidizing agents, alkalines, reducing agents, reactive halogens, or reactive metals.

REACTIVITY: Polymerization is not known to occur under normal temperatures and pressures. Not reactive with water.

HAZARDOUS DECOMPOSITION PRODUCTS: None under normal temperatures and pressures. See also **SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.**

SECTION 11: TOXICOLOGICAL INFORMATION
--

SENSITIZATION: Based on best current information, there is no known human sensitization associated with this product.

MUTAGENICITY: Based on best current information, there is no known mutagenicity associated with this product.

CARCINOGENICITY: Based on best current information, there is no known carcinogenicity as regulated by OSHA; as categorized by ACGIH A1 or A2 substances; as categorized by IARC Group 1, Group 2A, or Group 2B agents; or as listed by NTP as either known carcinogens or substances for which there is limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals.

REPRODUCTIVE TOXICITY: Based on best current information, there is no known reproductive toxicity associated with this product.

TERATOGENICITY: Based on best current information, there is no known teratogenicity associated with this product.

TOXICOLOGICALLY SYNERGISTIC PRODUCT(S): Based on best current information, there are no known toxicologically synergistic products associated with this product.

ARMAKLEEN Rust Remover
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY: No specific data. Low pH (acidity) of product may be harmful to aquatic life.

OCTANOL/WATER

PARTITION COEFFICIENT: Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

DISPOSAL: Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding recycling or proper disposal.

USEPA WASTE CODE(S): D002

Based on available data, this information applies to the product as supplied to the user. Processing, use, or contamination by the user may change the waste code(s) applicable to the disposal of this product.

SECTION 14: TRANSPORT INFORMATION

DOT: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Contains Phosphoric Acid), 8, UN 3264, II

TDG: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Contains Phosphoric Acid), 8, UN 3264, II

EMERGENCY RESPONSE GUIDE NUMBER: Not applicable.
Reference *North American Emergency Response Guidebook*

SECTION 15: REGULATORY INFORMATION

USA REGULATIONS

VOLATILE ORGANIC COMPOUNDS (AS REGULATED):

3.28 WT%; .39 LB/US gallon; 47 g/L As per 40 CFR Part 51.100(s)
Product Vapor Pressure @20°C = 11 mmHg
Product does not contain photochemically reactive solvents

SARA SECTIONS 302 AND 304: This product does not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

ARMAKLEEN Rust Remover

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

SARA SECTIONS 311 AND 312: This product poses the following health hazards as defined in 40 CFR Part 370 and is subject to the requirements of sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA):
Immediate (Acute) Health Hazard

SARA SECTION 313: This product does not contain toxic chemicals subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

CERCLA: This product contains the following "hazardous substance" listed under the Comprehensive Environmental Response, compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4 with the following reportable quantity (RQ):

<u>Material</u>	<u>CAS</u>	<u>RQ</u>
Phosphoric Acid	7664-38-2	5000 LB (454 kg)

TSCA: All the components of this product are listed on, or are automatically included as "naturally occurring chemical substances" on, or are exempted from the requirement to be listed on, the TSCA Inventory.

CALIFORNIA: This product does not contain detectable amounts of any chemical known to the State of California to cause cancer.

This product does not contain detectable amounts of any chemical known to the State of California to cause birth defects or other reproductive harm.

CANADIAN REGULATIONS

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS: E

CANADIAN ENVIRONMENTAL PROTECTION ACT

(CEPA): All the components of this product are listed on, or are automatically included as "substances occurring in nature" on, or are exempted from the requirement to be listed on, the Canadian Domestic Substances List (DSL).

ARMAKLEEN Rust Remover

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

SECTION 16: OTHER INFORMATION

REVISION INFORMATION: Regulatory Review of Content. Section 1, Revision Date; Section 2, Information on Ingredients; Section 12, Ecological Information; Section 15, Regulatory.

LABEL/OTHER INFORMATION: Not available.

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, The ArmaKleen Company assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either express or implied, or merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers. The data contained on this sheet apply to the product as supplied to the user.